

Interactive panel designed to provide maximum control in challenging situations

SPECIFICATIONS		
	Medium	Large
Chassis		
Dimensions (h x w x d)	1066 x 675 x 140mm	1433 x 879 x 140 mm
Material - Frame	3mm steel, powder coated	3mm steel, powder coated
Material - screen	10mm toughened glass	10mm toughened glass
Weight	45kg (approximately)	72kg (approximately)
Strength norm	IEC 62262 - IK10	IEC 62262 - IK10
Display		
Screen size	32 inch (81cm)	48 inch (124cm)
Resolution	1920 x 1080 (Full HD)	1920 x 1080 (Full HD)
Orientation	Portrait	Portrait
Touch		
Technology	Projected Capacitive	Projected Capacitive
Touch Resolution	2-3mm	2-3mm
Latency	<10 ms	<10ms
Audio		
Speakers	Hidden	Hidden
Range	60 - 20,000 Hz	60 - 20,000 Hz
Output power	2 x 15 Watt	2 x 15 Watt
Processing Unit		
Processor	Intel i3	Intel i3
Operating System	Windows 11 IoT Enterprise	Windows 11 IoT Enterprise
Power		
Rating	100 - 240 Volt (single phase, 50/60 Hz)	100 - 240 Volt (single phase, 50/60Hz)
Nominal/Maximal	80 Watt/120 Watt	100 Watt/140 Watt
Sleep mode	30 Watt	30 Watt
Environmental		
IP Rating	IPx5	IPx5
Operating temperature	0 - 35 degrees celsius	0 - 35 degrees celsius

Further technical drawings/models are available on request.