

## Safevent® Vertical

### Our vertical sliding anti-ligature window for mental health environments

The original and multi award-winning anti-ligature Safevent® in a vertical design. Trusted by over 80% of NHS Trusts and widely specified in supervised care environments worldwide.

The Safevent® - a benchmark product - was the first of its kind. Originally designed over 2 decades ago, it has been continuously refined in conjunction with clinicians, facilities managers, architects and service users since 2005.

The Safevent Vertical delivers all the trusted performance and safety features of the original Safevent® system in a space-saving, vertical format.

A popular choice within heritage projects offering a sympathetic alternative to traditional Victorian sliding sash and Georgian bar windows. Its discreet and unobtrusive design helps solve planning challenges with listed buildings and sensitive refurbishment schemes.



Britplas patented design



Anti-ligature multitask® handle



10mm toughened glass for optimum strength



Anti-ligature



Lock open or shut at any point



GlassShield® for enhanced robustness



Anti-contraband



External access sash for safe cleaning



10 Year Warranty\*



Maximum ventilation



Finished in any RAL colour / BS powder



Adopted by over 80% of NHS Trusts



Stainless steel fixed mesh for optimum security



Dual Colour



Annex B and BRE 2 tonne mesh tested



5 day replacement turnaround†



Vertical sliding sash



Optional integrated blinds



Available with a range of cills

\* Subject to terms

† Subject to supply of materials

## TECHNICAL SPEC

## Safevent® Vertical



INTERNAL VIEW  
(shown in half open position)

## EASY ACCESS FOR CLEANING

Safevent Access variant has an external sliding sash with an opening frame to allow direct access to the inside face of the glass and the outside of the mesh for easy cleaning and maintenance.

## SLIDING EXTERNAL SASH

Sliding external sash keeps moving parts to the outside of the window and maintains a simple internal surface.

## FIXED MESH

Stainless steel visomesh is permanently fixed into the frame to help eliminate frame gaps which may be used to create ligature points.



EXTERNAL VIEW  
(with Access sash in open position for cleaning)

## ULTRA SLIM PROFILE

To maximise light, reduce sightlines and provide enhanced thermal properties.

## MULTASK HANDLE

Single piece of hardware which does the job of a winder, patient thumb lock and staff lock.

## PERFORMANCE

## Weather

Tested to BS 6375 - 1:2009

Air Permeability	Class 2
Watertightness	Class E1050
Resistance to windload	Class C5

## Environmental

Tested in accordance with BS EN ISO 10077-1

U-Value	≤ 1.8 - 2.2 W/m <sup>2</sup> °K based on recommended glazing spec and size
Green Guide Rating	C

## Security

Medium Environmental Design Guide

STS202 BR1-4 (additional spec required, on request)

Tested by many NHS Trusts to replicate aggressive and continuous attack (video evidence available)

AMAA 2,000 ft/lbs (additional spec required on request)



INTERNAL VIEW



EXTERNAL VIEW

Full Revit/BIM integration is available for all Safevent window models.

Further technical drawings/models are available on request.

## TECHNICAL SPEC

## Safevent® Vertical

## COMPONENTS

## Frame

Profile	Bespoke aluminium profile extruded from aluminium alloy 6060/6063 T5/T6 and compliant with BS EN 12020-2: 2001/BS 755-9: 2001
Finish	All RAL / BS powder range / dual colour / bespoke finishes available to BS EN 12206-1:2021 Anodising to BS EN 12373 and BS 3987
Thermal Break	Polyamide strips PA 6.6 25
UK Patent	2446730
Standard cill options	125mm, 159mm, 200mm, 250mm (bespoke options available on request)

## Glazing options

Further options available on request

Standard - Fixed Unit	- 6.8mm laminated soft coat (external)
	- 20mm argon filled warm edge spacer
	- 10mm toughened (internal)
Standard - Sash	- 6mm toughened (internal) (depending on size/weight)
	- 20mm argon filled warm edge spacer
	- 6mm toughened soft coat (external)
G-Value	Standard - 0.45-0.48* Solar - 0.32-0.37*
Light Transmittance	Standard - 68-71%
*Variations	Performance varies by glass specification. Combinations between 32-42mm available upon request
Performance Applications	Self clean, Sand-blast, Solar, Mirror film, Obscure (full or partial) and Safety film

## Visomesh

Anti-tamper and anti-ligature 1.5mm thick stainless steel mesh. Double pressed for better vision and smoother finish. Black 9005 PPC finish as standard. Other PPC / printed artwork finishes available on request.

Perforation 2mm diameter holes to 3mm centres giving 40.3% open area

## Blinds

Integral Blinds Electronically operated (20mm spacer required)

## Hardware

Option 1	Multask handle (stainless steel) <a href="#">Click here for demo</a>
Option 2	- Anti-ligature window winder
	- Flush key lock (staff)
	- Manual thumb turn lock (patient)
Locks (external sash)	- Concealed key locks x2
Tricklevent Option	Anti-ligature permanently open

## Fixings

In strict accordance with the relevant British Standards, including BS 6262, fixings to be positioned 150mm from each corner, mullion, transom and at centres not exceeding 300mm or as advised dependent on structure.

**Important:** The information above is provided for guidance purposes only. It is provided subject to contract and no representation or warranty is made or intended. The window should be assessed or tested by each Client to ensure it meets the requirement of their patient group and intended use.

**Anti-ligature disclaimer:** This product may have varying degrees of anti-ligature characteristics. Any anti-ligature characteristics there may be are only intended to supplement and not replace or be an alternative to appropriate risk assessment and supervision of those who may be at risk. Other necessary protective measures may be required in the specific circumstances of usage. The customer must satisfy itself that the product(s) are suitable for their intended use. Britplas does not offer any products for sale as being 'ligature-free' and to the fullest extent permissible under applicable law it will not be liable for any claims connected to or arising from the attachment of ligatures on its products.

## OTHER

## Warranties

12 month warranty (extended warranty available)

10 year warranty (subject to terms - available as an extension to an existing warranty or on new windows)

## Quality

Manufactured and installed in accordance with ISO 9001:2008 (certificate available)

## Sustainability

All profiles used are environmentally sustainable and can be fully recycled supporting building energy performance

## Intellectual Property

Window patent EP-UK2013435  
Multask handle patent 2577180  
GlassShield trademark UK00003670222  
GlassShield patent 2596528

**For further product info and video demonstrations please visit <https://britplas.com/products/mental-health/safevent-window/>**