

Safevent® Access uPVC (SAP)

Our most advanced anti-ligature window for mental health environments



INTERNAL VIEW
(half open position)

EASY ACCESS FOR CLEANING

Safevent Access variant has an external sliding sash with an opening frame to allow direct access to the inside face of the glass and the outside of the mesh for easy cleaning and maintenance.

SLIDING EXTERNAL SASH

Sliding external sash keeps moving parts to the outside of the window and maintains a simple internal surface.

FIXED MESH

Stainless steel visomesh is permanently fixed into the frame to help eliminate frame gaps which may be used to create ligature points.

ULTRA SLIM PROFILE

To maximise light, reduce sightlines and provide enhanced thermal properties.

MULTASK HANDLE

Single piece of hardware which does the job of a winder, patient thumb lock and staff lock, to reduce ligature risk (optional).



EXTERNAL VIEW
(with Access sash shown in open position for cleaning)

| PERFORMANCE | |
|--|--|
| Weather | |
| Tested to BS 6375 - 1:2009 | |
| Air Permeability (ENG1026) | Class 3 |
| Watertightness (ENG1027) | Class 8A |
| Resistance to windload (EN12211) | Class CE2000 |
| Environmental | |
| Tested in accordance with BS EN ISO 10077-1 | |
| U-Value | ≤ 1.6 - 2.0 W/m ² °K based on recommended glazing spec |
| Green Guide Rating | A+ |
| Security | |
| Secure by Design compliance | PAS 24 |
| Medium Environmental Design Guide | |
| Tested by many NHS Trusts to replicate aggressive and continuous attack (video evidence available) | |



INTERNAL VIEW



EXTERNAL VIEW

Full Revit/BIM integration is available for all Safevent window models.
Further technical drawings/models are available on request.

Safevent® Access uPVC (SAP)

| COMPONENTS | |
|---|---|
| Frame | |
| Profile | Eurocell Eurologik 70 Profile |
| Finish | White as standard or any paint finish RAL |
| UK Patent | 2446730 |
| Standard cill options | 85mm, 151mm, 181mm, 222mm (bespoke options available on request) |
| Glazing options | |
| Further options available on request | |
| Standard - Fixed Unit | - 6.8mm laminated soft coat (external) |
| | - 12mm argon filled warm edge spacer |
| | - 10mm toughened (internal) |
| Standard - Sash | - 6mm toughened soft coat (external) |
| | - 18mm argon filled warm edge spacer |
| | - 4mm toughened (internal) |
| G-Value | Standard - 0.45-0.48* Solar - 0.32-0.37* |
| Light Transmittance | Standard - 68-71%* |
| *Variations | Performance varies by glass specification. Combinations available up to 28mm. |
| Performance Applications | Self clean, Sand-blast, Solar, Mirror film, Obscure (full or partial) and Safety film |
| Visomesh | |
| Anti-tamper and anti-ligature 1.5mm thick stainless steel mesh. Double pressed for better vision and smoother finish. Black 9005 PPC finish as standard. Other PPC / printed artwork finishes available on request. | |
| Perforation | 2mm diameter holes to 3mm centres giving 40.3% open area |
| Blinds | |
| Integral Blinds | Not available in uPVC profile |
| Hardware | |
| Option 1 | Multitask handle (stainless steel) Click here for demo |
| Option 2 | - Anti-ligature window winder |
| | - Flush key lock (staff) |
| | - Manual thumb turn lock (patient) |
| Locks (external sash) | - Concealed key locks x 2 |
| Tricklevent Option | Anti-ligature permanently open |
| Fixings | |
| In strict accordance with the relevant British Standards, including BS 6262, fixings to be positioned 150mm from each corner, mullion, transom and at centres not exceeding 400mm or as advised dependent on structure. | |

| OTHER |
|--|
| Warranties |
| 12 month warranty (extendable by maintenance contract) |
| Parts warranties up to 25 years and design life up to 35 years |
| Quality |
| Manufactured and installed in accordance with ISO 9001:2008 (certificate available) |
| Sustainability |
| All profiles used are environmentally sustainable and can be fully recycled supporting building energy performance |

For further product info and video demonstrations please visit <https://britplas.com/products/specialist-windows/safevent-window/>

Important: The information above is provided for guidance purposes only. It is provided subject to contract and no representation or warranty is made or intended. The window should be assessed or tested by each Client to ensure it meets the requirement of their patient group and intended use.

Anti-ligature disclaimer: This product may have varying degrees of anti-ligature characteristics. Any anti-ligature characteristics there may be are only intended to supplement and not replace or be an alternative to appropriate risk assessment and supervision of those who may be at risk. Other necessary protective measures may be required in the specific circumstances of usage. The customer must satisfy itself that the product(s) are suitable for their intended use. Britplas does not offer any products for sale as being 'ligature-free' and to the fullest extent permissible under applicable law it will not be liable for any claims connected to or arising from the attachment of ligatures on its products.